

# Material Safety Data Sheet

11/21/01

**PRODUCT IDENTITY: #3001 Normal HS Clear Coat Activator**

## -----Section I----- – Manufacturer Information

Manufacturer Name: Southern Polyurethanes, Inc.

NFPA Ratings

Address:

2289 Arbor Hill Rd.

Canton, GA 30115

Emergency Telephone

CHEMTREC-1-800-424-9300

Telephone for information

770 720-6986

|              |
|--------------|
| Health       |
| Flammability |
| Reactivity   |
| Personal     |
| Protection   |

## Section II-Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name)

|                            | CAS#       | OSHA PEL  | ACGIH TLV | Wt %  |
|----------------------------|------------|-----------|-----------|-------|
| BUTYL ACETATE              | 123-86-4   | 150 ppm   | 150 ppm   | 15/20 |
| LIGHT AROMATIC NAPHTHA     | 64742-95-6 | 100 ppm   | 100 ppm   | 5/10  |
| METHOXY-2-ACETOXYPROPANE   | 108-65-6   | Not est.  | Not est.  | 25/30 |
| HEXAMETHYLENE DIISOCYANATE | 822-06-0   | Not est.  | 0.005 ppm | <0.1  |
| ISOPHRONE DIISOCYANATE     | 4098-71-9  | 0.005 ppm | 0.005 ppm | <0.1  |
|                            |            |           |           |       |

## Material Safety Data Sheet

\* SARA 313 listed chemical

DOT SHIPPING: FLAMMABLE LIQUID; PAINT RELATED MATERIAL

### Section

#### **Physical/Chemical Characteristics**

---

Boiling Point: 248° F  
mmHg

Specific Gravity (H<sub>2</sub>O = 1): 1.03

Vapor pressure (mmHg @ 70°F):

Vapor Density (Air = 1): Heavier than Air    Evaporation Rate:(butyl acetate = 1) >1    V.O.C.: 4.1 #/gal

Appearance and Odor: Water white Liquid, Solvent Odor  
#/gal

V.O.C. less exempt solvents:

### **Section IV-Fire and Explosion Hazard**

#### **Data**

---

Flash Point (Method Used): 76°F (TCC)

Flammable Limits: LEL 1.7    UEL 7.6

Extinguishing Media

Class B extinguisher, Carbon Dioxide, Dry Chemical, Foam Special Fire Fighting Procedures

Water spray can be used to cool containers exposed to fire. Clear area of unprotected personnel. Fire fighters are wear self-contained breathing apparatus and proper protection gear. Keep containers closed tightly. Isolate from sparks, and open flames.

Unusual Fire and Explosion Hazards

Closed containers may explode when exposed to extreme heat.

### **Section V- Reactivity**

#### **Data**

---

Stability – Unstable: Conditions to Avoid: Sources of ignition

Stable: Yes

Incompatibility (Materials to Avoid): Strong Oxidizers

Hazardous Decomposition products: Carbon monoxide, Carbon dioxide, and Oxides of nitrogen

Hazardous Polymerization: Will not occur

### **Section VI- Health Hazard**

#### **Data**

---

Routes of Entry: Inhalation? Yes    Skin? Yes    Ingestion? Yes

Health Hazards (Acute and Chronic)

## Material Safety Data Sheet

May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible. Long exposure (years) vapor may cause lung, liver or kidney damage. The solvents listed have been reported to affect the central nervous system. Signs and Symptoms of Exposure: Inhalation - difficulty in breathing; Skin – redness; Ingestion - vomiting

Medical Conditions Generally Aggravated by Exposure: Heart Disease; respiratory disorders.

Emergency and First Aid Procedures:

If overcome by vapors give oxygen. Do not induce vomiting. Wash eyes with large quantities of water.

Wash skin with soap and water.

Carcinogenicity NTP? No IARC Monographs? No OSHA? No

### **Section VII - Precautions for Safe handling and Use**

Steps to be taken in Case Material is Released or Spilled- -Eliminate all sources. Scrape up with NONSPARKING tool. Remove outside area away from ignition sources. FLASHBACK POSSIBLE.

Waste Disposal Method--

Dispose as hazardous waste in accordance with EPA RCRA.

Precautions to be taken in Handling and Storing- Keep away from heat, sparks or open flame. Store at temperatures below 120F

Other Precautions - -

Excessive skin contact may defat skin causing dermatitis.

Respiratory Protection (Specify Type):

Self contained breathing apparatus if above TLV limit exceeding.

Ventilation Local Exhaust:

YES Mechanical (General)

Protective Gloves: Neoprene, Viton

Eye Protection: Wear eye protection.

Other Protective Clothing or Equipment: N/A Work/Hygienic Practices:

Do not smoke while using. Wash your hands after every use.

Avoid unnecessary exposure and removal of the material from skin and clothing.

\* SARA

## Material Safety Data Sheet

All chemical compounds marked with an asterisk (\*) are toxic chemicals subject to the reporting requirements Section 313 of Title III of the Super Fund Amendments and Reauthorization Act (SARA) of 1990 and 40 CFR 372. You must notify each person to whom this mixture or trade name product is sold. This statement must be part of this Material Data Safety Sheet. This statement must not be detached. Any copy or redistribution of this Material Data Safety Sheet shall include this statement.